HDL-MVD02101P

2-wire IP Villa Door Station



- · Anodized alumimum front panel
- \cdot CMOS low illumination 2MP HD colorful 160° fisheye camera \cdot Video intercom function
- Access control function that supports two locks
- Mobile phone app, talk to the visitor or unlock the door remotely on your phone
- \cdot Compatible with 2-wire interface & RJ45

interface • IK07&IP65

- Support H.265
- Support surface and flush mount
- PoE



Technical Specification		
System		
Main Processor	Embedded processor	
Operating System	Embedded Linux Operation System	
Button Type	Mechanical	
Interoperability	ONVIF; CGI	
Network Protocol	SIP; P2P; IPv4; UPnP; SNMP; DNS; DDNS; RTSP; RTP; TCP; UDP	
Basic		
Camera	1/2.5" 2MP CMOS Low Illumination HD Colorful Fisheye Camera	
Field of View	Horizontal: 168.6°; vertical: 87.1; diagonal:176.7°	
Focal Length	1.9 mm	
WDR	120 dB	
Noise Reduction	3D NR	
Video Compression	H.265	
Video Resolution	50Hz: Main Stream (720P@25 fps), sub stream (1080P@25 fps) 60Hz: Main Stream (720P@30 fps), sub stream (1080P@30 fps)	
Video Frame Rate	25 fps	
Video Bit Rate	256 Kbps to 4 Mbps	
Light Compensation	Auto IR	

Day/Night	Auto (ICR)
Audio Compression	G.711u
Audio Input	1 channel
Audio Output	Built-in speaker
Audio Mode	2-way voice communication
Audio Enhancement	Echo suppression/digital noise reduction
Audio Bit Rate	16 KHz, 16 Bit
Status Indicator Light	3
Port	
Electric Lock	1
Alarm Output	1
Power Output	1-ch 12 VDC 100mA
Exit Button	1
Door Status Detection	1
Lock Control	1
Network Port	One RJ45 10M/100M network port
General	
Appearance color	Silver
Power Supply	Dahua 2-wire switch (max. power supply distance 50 m) DC 48V 1A Standard PoE

VTO2 Series | HDL-MVDO2101P

Power Adapter	Optional
Installation	Flush/surface mount
Certifications	CE; FCC; UL
Accessory	Flush/surface mount
Product Dimensions	130 mm × 96 mm × 28.5 mm (5.12" × 3.78" × 1.12")
Protection	IK07; IP65
Operating Temperature	-30°C to +60°C (-22°F to 140°F)
Operating Humidity	10%–90% (RH, non-condensing)
Operating Altitude	0 m-3000 m
Power Consumption	≤ 12W
Net Weight	0.35 kg (0.77 lb)
Gross Weight	0.4 kg (0.88 lb)

Elevenel Cable 2-wire Cable	

Application

Ordering Information Type Model Description Two-wire IP Villa Door Station HDL-MVDO2101P 2Mp Non Issue card 2-wire IP Villa Door Station VTM114 Flush Mounted Box Accessories VTM115 Surface Mounted Box VTM05R Surface-mounted rain cover for VTO2202F

Dimensions (mm[inch])









