# **Datasheet**

# ML26 Accent Light

MODULINE Linear System Inset ML26-AL280-13W Type:



#### General

- Indoor
- Accent Light
- Fixed
- Profile Inset Version: square
- · Housing: black · Reflector: black
- · System Output: 1000lm
- IP 20



#### LED

- · 2700K
- CRI90
- 1400lm
- 50000h@L80B10
- SDCM: 3

## **Optics**

· Beam angle: 20° • UGR <19

# **Electric**

• LED Driver: ON-OFF • LED Power: 12W · System Power: 13W

• 48V

#### Dimensions


· Measurement: 284mm x 22mm

· Height: 43mm

# Description

MODULINE 26 Linear System Accent Light Inset with ON-OFF; black painted finish (RAL 9005) and black reflector; LED 12W; measurement 284mm x 22mm; height of the profile inset 43mm; CCT 2700K with an LED Output of 1400lm; high color rendering at an index of CRI90; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient OSRAM LED Chips; 5 years warranty; precise beam characteristic with 20° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19); degree of housing protection according to DIN EN 60529 (IP20)

### **Light distribution**



# **Technical drawing**





**(€** RoHS







The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10% those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of HDL Automation apply.

