

## ML26 General Light



**Type:** MODULINE Linear System Inset ML26-GL560-13W

### General

- Indoor
- General Light
- Fixed
- Profile Inset
- Version: square
- Housing: black
- System Output: 800lm
- IP 20

### Description

MODULINE 26 Linear System General Light Inset with ON-OFF; black painted finish (RAL 9005); LED 12W; measurement 564mm x 22mm; height of the profile inset 43mm; CCT 3000K with an LED Output of 1200lm; high color rendering at an index of CRI90; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient SAMSUNG LED Chips; 5 years warranty; wide beam characteristic with 110° beam angle; degree of housing protection according to DIN EN 60529 (IP20)

### LED



- 3000K
- CRI90
- 1200lm
- 50000h@L80B10
- SDCM: 3

### Optics

- Beam angle: 110°


### Electric

- LED Driver: ON-OFF
- LED Power: 12W
- System Power: 13W
- 48V

### Dimensions

- Measurement: 564mm x 22mm
- Height: 43mm

### Light distribution



### Technical drawing



CB

CE

RoHS



Driver

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10% those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of HDL Automation apply.