

HD-TH3055



General

- Indoor
- Spotlight
- Recessed
- Version: round
- Housing: white
- Reflector: white/black/chrome
- System Output: 420lm
- IP 20

LED

- 2800K-6000K
- CRI>90
- 50000h@L80B10
- SDCM: 3

Optics

- Beam angle: 24°/36°
- UGR <13
- Honeycomb mesh

Electric

- LED Driver: none
- LED Power: 7W
- 36V
- 150mA


Dimensions

- Measurement: Ø60mm
- Cutout: Ø55mm
- Height: 80mm
- Pivot: max. 30°
- Rotation: 355°


Description

- Round adjustable Recessed Spotlight (55 Series) made of die-cast aluminum with white powder-coating finish (RAL 9016) and white/black/chrome reflector;
- Work with DALI dimming driver;
- LED 7W;
- Measurement Ø60mm; ceiling cutout of Ø55mm with a narrow mounting trim;
- High color rendering at an index of CRI90;
- After a lifetime of 50000h min. 80% of the luminous flux;
- 5 years warranty;
- Beam characteristic with 24°/36° beam angles;
- Lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1(UGR<13);
- Degree of housing protection according to DIN EN 60529 (IP20).


Light distribution



7W24°359lm				
Lux				
h(m)	d(m)	Em	E _{max}	
1	0.38	1414	2105	
2	0.79	353.4	526.3	
3	1.19	157.1	233.9	
4	1.59	88.35	131.6	
5	1.99	56.54	84.21	




7W36°367lm				
Lux				
h(m)	d(m)	Em	E _{max}	
1	0.56	848.1	1226	
2	1.12	212	306.5	
3	1.69	94.23	136.2	
4	2.25	53.01	76.63	
5	2.81	33.92	49.05	



Ø55mm

Technical drawing



The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors.