

CX8001



General

- Indoor
- General Light
- Install onto the track
- Profile Inset
- Housing: black
- System Output: 360lm
- IP 20

LED



- 2800K-6000K
- CRI>90
- 50000h@L80B10
- SDCM: 3

Optics

- Beam angle: 16°/24°/36°
- UGR <15

Electric

- LED Driver: DALI
- LED Power: 6W
- 36V
- 150mA




Dimensions

- Measurement: Ø38mm
- Height: 495mm

Description

- Magnetic Suspended Light Inset with DALI dimming driver;
- Black painted finish (RAL 9005);
- LED 6W;
- Measurement Ø38mm; height of the suspended light is 495mm; wide of the profile inset is 186mm;
- High color rendering at an index of CRI90;
- After a lifetime of 50000h min. 80% of the luminous flux with energy efficient Luminus LED Chips;
- 5 years warranty;
- Precise beam characteristic with 16°/24°/36° beam angles;
- Lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<15);
- Degree of housing protection according to DIN EN 60529 (IP20).

Light distribution



6W 16°				
Lux				
h(m)	d(m)	Em	Emax	
1	0.25	2433	3518	
2	0.50	608.3	879.5	
3	0.75	270.3	390.9	

6W 24°				
Lux				
h(m)	d(m)	Em	Emax	
1	0.54	2208	3424	
2	1.08	552	856	
3	1.62	245.4	380.4	

6W 36°				
Lux				
h(m)	d(m)	Em	Emax	
1	0.7	1287	1853	
2	1.4	321.8	463.3	
3	2.1	143	205.9	



CB

CE


RoHS



Driver



Technical drawing



The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors.